



MAINTENANCE OF LEVEL TOP POLISHED FLOORS



POST FIXTURING

Clean the floor thoroughly. Using a high-speed, propane burnisher equipped with a diamond impregnated pad, polish the floor to achieved finish. Applying additional UltraSil™ LI+ during this process might be required to achieve desired level of gloss. Protect polished floors with Euclid Chemical Ultraguard™, following standard installation instructions.

FIRST SIX MONTHS

Clean the floor often during the first several months after the application and wash on a regular basis thereafter. The more buffing the Level Top floor receives, the greater the sheen of the floor will be.

DETERGENTS / STRIPPERS

Use mild (neutral to high pH) soaps or detergents to clean your Level Top floor. Do not use acidic cleaners or detergents. Spot clean to remove grease, oil, or tire marks.

PROTECTION

Protect the floor from spills as much as possible. The sealing and densifying action of UltraSil™ LI+ and Ultraguard™ will increase over the first year of service, but good housekeeping practices and quick clean-up of spills are always recommended to keep the floor looking good. The longer the spill remains on the floor, the more likely it is to stain.

MAINTENANCE

The frequency of routine maintenance should be scheduled based on the type and amount of traffic, as well as exposure to abrasive chemicals and/or materials. The use of a walk-behind or ride-on floor scrubber to clean and buff a polished Level Top floor will produce the best results, and is most practical on large floors.

WAX

An additional application of a Increte High Gloss may be used to provide another layer of sacrificial protection of a polished Level Top floor.

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.



DETAILED MAINTENANCE PLAN FOR LEVEL TOP POLISHED FLOORS



DAILY

Keep floors clean using dry dust mops or microfiber mop. Clean up spills immediately by using a mop and bucket/spray bottle with a mild (neutral PH) soap or detergent diluted 1 oz per gallon of clean water. Remove all residual ponding water and cleaning agents. Spot clean any concentrated stains as needed. **DO NOT USE** any abrasive cleaning pads or citrus based cleaning agents which may etch the the surface and reduce the protection of the Densifer and Guards.

WEEKLY

Fully clean the floor weekly with mop and bucket and a mild (neutral PH) soap or detergent diluted 1 oz per gallon of clean water. The use of a walk-behind or ride-on floor scrubber to clean and buff a polished Level Top floor will produce the best results, and is most practical on large floors. Remove all residual ponding water and cleaning agents.

MONTHLY

Perform a walk-through to identify any possible excessive wearing areas or deep staining that may require attention outside of this maintenance plan. Contact Euclid Chemical for addition support.

Due to varying traffic frequency and exposure to abrasive chemicals and/or materials, timetables for the above procedures may need to be adjusted to fit the needs of each floor.

6 MONTHS - 1 YEAR

Re-sealing with UltraSil™ Li+ and Ultraguard™ followed by a high speed burnish is recommended. This may involve stripping any wax that has been applied prior to resealing.

ANNUALLY

Perform a walk-through, possibly with a Euclid Chemical Sales Representative, to identify any possible excessive wearing areas or deep staining that may require attention. A second densifer and guard application could be considered based on the type and amount of traffic, as well as exposure to abrasive chemicals and/or materials. Contact Euclid Chemical for assistance in making this assessment. Although seldom required, in very high traffic areas, a full re-grind & polish of the Level Top flooring system, as well as a second densifer and guard application could be required.

ADDED PROTECTION AT ANY TIME

Euco® Diamond Hard™ may be used prior to the application of the Ultraguard™ for added stain protection. Contact Euclid Chemical for addition support with this application.

An additional application Increte High Gloss Wax can be used and will provide another layer of sacrificial protection of the Level Top flooring system. Contact Euclid Chemical for addition support with this application.

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.