



# INCRETE HIGH GLOSS WAX

## PROTECTIVE FINISH FOR SEALED CONCRETE FLOORS

### PACKAGING

1 gal (3.8 L) and 5 gal (18.0 L) units

### YIELD

Approximately 1,500 to 2,000 ft<sup>2</sup>/gal (24.6 to 48.9 m<sup>2</sup>/L) per coat depending on type and texture of surface and method of application.

### APPEARANCE

White liquid that dries clear

### CLEAN UP

Clean tools and equipment with water before the material hardens.

### SHELF LIFE

2 years in original, unopened containers

### BRIEF OVERVIEW

INCRETE HIGH GLOSS WAX is a clear, durable, acrylic wax that leaves a beautiful high-gloss finish that, when properly maintained, resists surface abuse. Heel mark, stain, and abrasion resistant, INCRETE HIGH GLOSS WAX can be buffed to maintain a high gloss finish.

### PRODUCT CHARACTERISTICS

#### ADVANTAGES

- High gloss
- Protects finish
- Resists heel marks
- Dries quickly
- Suitable for use over all acrylic, epoxy, urethane, polyurea/polyaspartic and other film-forming coatings
- Provides protection to sealers and coatings
- Increases surface reflectivity
- Makes floor cleaning effortless

#### COMMON USES

- Interior flooring
- Restore shine to scratched coatings
- Protection to floor coatings

#### COMMON APPLICATION METHODS

- Wax applicator
- Microfiber
- Lamb's wool mop

### DIRECTIONS FOR USE

INCRETE HIGH GLOSS WAX can be used on all interior, sealed concrete floors and slabs including terrazzo, brick, Mexican tile, ceramic tile, slate, adobe, and quarry tile as well as parquet and sealed wood.

#### APPLICATION

Sweep and mop floor and remove old wax (if needed). Let surface dry and apply INCRETE HIGH GLOSS WAX with a wax applicator, microfiber, or lamb's wool mop.

Apply additional coats in heavy-traffic areas or where needed allowing 30-minute intervals between coats. Repeated coats will produce a very durable, high-gloss finish. INCRETE HIGH GLOSS WAX can be removed using a wax stripper.

---

## PRECAUTIONS/LIMITATIONS

- Allow newly sealed or coated floors to cure completely prior to application.
- Do not apply directly to unsealed/densified concrete.
- For interior use only.
- Protect product from freezing.
- In all cases, consult the Safety Data Sheet before use.

Rev. 07.21

---

**WARRANTY:** The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.