



INCRETE MATTE ADD

FLATTENING ADDITIVE FOR ACRYLIC SEALERS

PACKAGING

1 lb (0.45 kg) and 15 lb (6.8 kg) units

YIELD

Approximately 1 scoop (enclosed) per 1 gal/3.8 L or 1 lb/5 gal (0.45 kg/18.9 L) of sealer.

APPEARANCE

Dry white powder

CLEAN UP

Vacuum or sweep spills

SHELF LIFE

4 years in original, unopened container

BRIEF OVERVIEW

INCRETE MATTE ADD is a colorless, finely-graded, polypropylene additive for sealers and coatings, that provides a low-gloss finish on concrete surfaces. INCRETE MATTE ADD may be stirred into standard solvent-based, acrylic sealers to turn any acrylic sealer into a low-gloss coating. Unlike many silica additives, INCRETE MATTE ADD will stay suspended in solution longer with no need for continuous stirring.

PRODUCT CHARACTERISTICS

ADVANTAGES

- Provides satin or matte finish
- Stirs in easily
- Will not clump in solvent-based sealers if mixed well.
- For use with INCRETE CLEAR SEAL, INCRETE CRYSTAL CLEAR VOC, INCRETE CONCRETE STAIN SEALER and Euclid Chemical's DIAMOND CLEAR OR SUPER DIAMOND CLEAR

COMMON USES

- Interior/Exterior
- Cuts gloss in solvent-based acrylic sealers

COMMON APPLICATION METHODS

- Stir into sealer of choice

TECHNICAL INFORMATION

Composition: Polypropylene powder

Particle Size: 325-mesh

DIRECTIONS FOR USE

INCRETE MATTE ADD can be used in most solvent-based, acrylic sealers and coatings where a low-gloss finish is desired.

STANDARD DOSAGE

1 scoop (enclosed) per 1 gal (3.8 L) or 1 lb/5 gal (0.45 kg/18.9 L) pail. Dosage may be varied to achieve the desired effect. Dosages greater than 1.5 scoops per gallon may cause excessive viscosity. Performance and results will vary based on sealer choice and application conditions. Perform jobsite tests for optimum results.

TESTING

Apply first coat of sealer without the addition of INCRETE MATTE ADD. Once first coat of sealer has dried, apply sealer with INCRETE MATTE ADD in an inconspicuous area and allow to dry to verify desired effect.

DIRECTIONS FOR USE CONT.

PROCEDURE

Mix sealer or coating to proper consistency. For best results, pour off 20-30% of the solvent-based material and slowly add recommended amount of INCRETE MATTE ADD while mechanically mixing and mix until completely dispersed. Then return flattened material to container and re-mix. If material is allowed to sit, re-mix before use. Apply sealer in thin, uniform coats. Results may vary depending on coating, substrate and application techniques.

PRECAUTIONS/LIMITATIONS

- For professional use only.
- Not recommended for use in water-based sealers.
- In all cases, consult the Safety Data Sheet before use.

Rev. 07.21

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.