

GRINDING AIDS

Master Format #: 00 00 00

EUCEM™ AEM 8

AIR ENTRAINING AND WORKABILITY AGENT FOR MASONRY CEMENTS



EUCLID CHEMICAL

PRODUCT INFORMATION

PACKAGING

Available in 55 gal (208 L) drums, 264 gal (1000 L) totes, and bulk

SHELF LIFE

12 months

TECHNICAL INFORMATION

Active ingredients:

Aqueous solution of organic components

Freezing Point: < -15°C

Flash Point: >100°C

DESCRIPTION

EUCEM AEM 8 is a grinding aid specifically formulated to entrain air into masonry type cements and improved the water retention characteristics.

PRODUCT CHARACTERISTICS

FEATURES & BENEFITS

- Strong tension-active action.
- Better control of air contents, optimised bubble size and spacing. Good air retention properties.
- Easier and more thorough mortar mixing.
- Improved trowelability.
- Improved flowability.
- Improved water tightness.
- Reduces plastic shrinkage (initial set).
- Improved physical properties of the ground material.
- Improved performance in both closed and open circuit systems at equal specific surface area or equal sieve residues.
- Powder flow characteristics are improved before, during and after storage.

APPLICATIONS

- Masonry type cements N, S and M.

TECNICAL INFORMATION

% Solids (ASTM C494)	Specific Gravity @ 77°F (25 °C) (ASTM D1298)	pH per Electrode @ 77°F (25 °C)
26.0 - 28.0	1.030 - 1.050	10.0 - 12.0

DIRECTIONS FOR USE

DOSAGE

The dosage range is typically between 0.08 and 0.2% per cement weight. Optimum dosage should be determined by plant trials and subsequent mortar evaluations.

PROCEDURE

Liquid admixture ready-to-use. A dosing pump is required to introduce the correct dosage into the mill. EUCEM AEM 8 may be introduced directly into the mill or onto the feed conveyor belt.

Our technicians are ready to provide advice and assistance in the use of EUCEM AEM 8.

PRECAUTIONS/LIMITATIONS

- The quality is guaranteed for 12 months starting from the manufacturing date provided the product is not altered with other chemicals.
- Do not mix with any other product.
- Refer to Safety Data Sheet for additional information.

Rev. 05.22

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.