

## JOINT SEALANTS

Master Format #: 07 92 13

# EUCOLASTIC PRIMER

## POLYURETHANE SEALANT PRIMER



**EUCLID CHEMICAL**

### PACKAGING

1 quart (0.95 L) unit, 12 per case  
Code: 073R 94 (MTO)

### APPROXIMATE COVERAGE

Estimated coverage is 2400 lineal ft/gal per 1/2" depth of double faced joint (193 linear m/L per 13 mm depth of double faced joint).

### CLEAN UP

Tools, equipment and general clean-up can be done with EUCO SOLVENT, acetone or toluene.

### SHELF LIFE

1 year in original, unopened container

### DESCRIPTION

EUCOLASTIC PRIMER is a single-component, fast drying liquid primer that prepares non-porous surfaces for the application of EUCOLASTIC 1NS and EUCOLASTIC 1SL. EUCOLASTIC PRIMER imparts a surface finish which is very receptive to urethane sealants.

### PRODUCT CHARACTERISTICS

#### FEATURES/BENEFITS

- Provides primer base for adhesion of EUCOLASTIC sealants
- Increases adhesion for use in immersion situations
- Seals porous surfaces increasing water tightness

#### PRIMARY APPLICATIONS

- To prepare surface for the adhesion of urethane sealants
- Assures a water resistant bond on porous and non-porous substrates

#### APPEARANCE

EUCOLASTIC PRIMER is a clear, one component liquid with a slight amber color.

#### TECHNICAL INFORMATION

EUCOLASTIC PRIMER will dry in 30 to 45 minutes @ 70 °F (21 °C). Primer must be completely dry before installation of a Eucolastic sealant.

If the EUCOLASTIC PRIMER becomes hard and glossy, the surface must be cleaned with solvent and reprimed.

---

## DIRECTIONS FOR USE

**Surface Preparation:** New concrete must be a minimum of 28 days old. The joint must be clean and sound. All oil, dirt, debris, paint and any other material that could be a bond breaker must be removed. The final step in cleaning should be the complete removal of all residue with a vacuum cleaner or by pressure washing. All joint facings must be dry and have an open surface texture with all curing compounds and sealers removed.

**Application:** EUCOLASTIC PRIMER should be applied liberally with a clean brush or roller, but do not allow the product to puddle or pond. Use with adequate ventilation.

---

## PRECAUTIONS/LIMITATIONS

- Keep containers sealed until ready to use.
- Opened containers have limited shelf life (less than 1 month).
- This product is amber in color and is noticeable on some surfaces. Care must be taken to apply only to areas that will be covered by final product.
- In all cases, consult the Safety Data Sheet before use.

Rev. 01.22

---

**WARRANTY:** The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.