



SAFETY DATA SHEET

1. Identification

Material name: EUCO SOLVENT
Material: 045 05

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Euclid Admixture Canada Inc.
2835 Grand-Allee
Saint Hubert QC J4T 2R4
CA

Contact person: EH&S Department
Telephone: (450)465-2233
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 3

Health Hazards

Acute toxicity (Inhalation - vapor) Category 4
Acute toxicity (Inhalation - dust and mist) Category 4
Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Germ Cell Mutagenicity Category 1B
Carcinogenicity Category 1B
Specific Target Organ Toxicity - Single Exposure Category 3¹
Aspiration Hazard Category 1

Target Organs

1. Respiratory tract irritation.

Unknown toxicity - Health

Acute toxicity, oral 4 %
Acute toxicity, dermal 16.01 %
Acute toxicity, inhalation, vapor 64.98 %
Acute toxicity, inhalation, dust or mist 65 %

Environmental Hazards



Acute hazards to the aquatic environment	Category 2
Chronic hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	63.47 %
Chronic hazards to the aquatic environment	54.5 %

Label Elements**Hazard Symbol:****Signal Word:** Danger**Hazard Statement:** Flammable liquid and vapor.
Harmful if inhaled.
Causes skin irritation.
Causes serious eye irritation.
May cause genetic defects.
May cause cancer.
May cause respiratory irritation.
May be fatal if swallowed and enters airways.
Toxic to aquatic life with long lasting effects.**Precautionary Statements****Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/...] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.**Response:** IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention. IF SWALLOWED:



Immediately call a POISON CENTER/doctor/... Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing. In case of fire: Use... to extinguish. Collect spillage.

Storage: Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Aromatic petroleum distillates	64742-95-6	20 - <50%
1,2,4-Trimethylbenzene	95-63-6	25 - <50%
1,3,5-Trimethylbenzene	108-67-8	10 - <20%
1,2,3-Trimethylbenzene	526-73-8	1 - <5%
Xylene	1330-20-7	1 - <5%
Cumene	98-82-8	1 - <2.5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures

Inhalation: Move to fresh air.

Skin Contact: Take off immediately all contaminated clothing. Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Ingestion: Rinse mouth. Call a physician or poison control center immediately. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Personal Protection for First-aid Responders: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed



Symptoms: Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Accidental release measures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

**7. Handling and storage****Handling**

Technical measures (e.g. Local and general ventilation): Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Safe handling advice: Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin.

Contact avoidance measures: No data available.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin.

Storage

Safe storage conditions: Store locked up. Store in a well-ventilated place. Store in a cool place.

Safe packaging materials: No data available.

8. Exposure controls/personal protection**Control Parameters****Occupational Exposure Limits**

Chemical Identity	Type	Exposure Limit Values	Source
1,2,4-Trimethylbenzene	REL	25 ppm 125 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	TWA	25 ppm 125 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	25 ppm 125 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	AN ESL	25 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011)
	ST ESL	140 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (02 2013)
	ST ESL	700 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (02 2013)
	AN ESL	125 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011)
	TWA PEL	25 ppm 125 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (08 2010)
	TWA	25 ppm	US. ACGIH Threshold Limit Values, as amended (2011)



1,3,5-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
1,2,3-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
Xylene	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	STEL	150 ppm	655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	100 ppm	435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	STEL	150 ppm	655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	ST ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011)
	ST ESL		80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011)
	AN ESL		42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011)
	AN ESL		180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011)
	STEL	150 ppm	655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (08 2010)
	TWA PEL	100 ppm	435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (08 2010)
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Cumene	TWA	50 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	50 ppm	245 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)



Chemical name	Type	Exposure Limit Values	Source
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
1,2,3-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,3-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,3-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Cumene	STEL	75 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm	Canada. British Columbia OELs. (Occupational



			Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cumene	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Cumene	TWA	50 ppm 246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)

Chemical name	Type	Exposure Limit Values	Source
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
1,2,3-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,3-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,3-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)



Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Cumene	STEL	75 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cumene	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Cumene	TWA	50 ppm 246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Toluene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Toluene	TWA	50 ppm 188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Benzene	STEL	2.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene	TWA	0.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	STEL	2.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Benzene	TWA	1 ppm 3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	STEL	5 ppm 15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

**Individual protection measures, such as personal protective equipment**

General information:	Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin.

9. Physical and chemical properties**Appearance**

Physical state:	liquid
Form:	liquid
Color:	Colorless
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	160 °C 320 °F
Flash Point:	44 °C 111 °F(Tag closed cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	7 %(V)
Flammability limit - lower (%):	1 %(V)
Explosive limit - upper:	No data available.
Explosive limit - lower:	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.



Relative density:	0.88
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	< 20.5 mm ² /s (40 °C 104 °F)

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes skin irritation.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

**Information on toxicological effects****Acute toxicity (list all possible routes of exposure)****Oral****Product:** ATEmix: 93,333.33 mg/kg**Dermal****Product:** ATEmix: 30,798.17 mg/kg**Inhalation****Product:** ATEmix: 11.01 mg/l
ATEmix : 1.5 mg/l**Repeated dose toxicity****Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Specified substance(s):**Aromatic petroleum
distillates in vivo (Rabbit): Irritating

1,2,4-Trimethylbenzene in vivo (Rabbit): Irritating

1,3,5-Trimethylbenzene in vivo (Rabbit): Irritating

Xylene in vivo (Rabbit): Moderate irritant

Cumene in vivo (Rabbit): Not irritant

Serious Eye Damage/Eye Irritation**Product:** No data available.**Specified substance(s):**Aromatic petroleum
distillates Rabbit, 24 - 72 hrs: Not irritating

1,2,4-Trimethylbenzene Rabbit, 30 min: Not irritating

1,3,5-Trimethylbenzene Rabbit, 30 min: Not irritating

Xylene Rabbit, 24 hrs: Moderately irritating

Cumene Rabbit, 24 hrs: Not irritating

Respiratory or Skin Sensitization**Product:** No data available.

**Carcinogenicity****Product:** May cause cancer.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Cumene Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Cumene Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity**In vitro****Product:** No data available.**In vivo****Product:** No data available.**Reproductive toxicity****Product:** No data available.**Specific Target Organ Toxicity - Single Exposure****Product:** No data available.**Specified substance(s):**

Cumene Inhalation - vapor: Category 3 with respiratory tract irritation.

Specific Target Organ Toxicity - Repeated Exposure**Product:** No data available.**Target Organs**

Specific Target Organ Toxicity - Single Exposure: Respiratory tract irritation.

Aspiration Hazard**Product:** May be fatal if swallowed and enters airways.**Other effects:** No data available.**12. Ecological information****Ecotoxicity:****Acute hazards to the aquatic environment:**

000000003936

**Fish****Product:** No data available.**Specified substance(s):**1,2,4-Trimethylbenzene LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 7.19 - 8.28 mg/l MortalityXylene LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l MortalityCumene LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 6.04 - 6.61 mg/l Mortality**Aquatic Invertebrates****Product:** No data available.**Specified substance(s):**Cumene LC 50 (Water flea (*Daphnia magna*), 48 h): 7.9 - 45.1 mg/l Mortality**Chronic hazards to the aquatic environment:****Fish****Product:** No data available.**Aquatic Invertebrates****Product:** No data available.**Toxicity to Aquatic Plants****Product:** No data available.**Persistence and Degradability****Biodegradation****Product:** No data available.**BOD/COD Ratio****Product:** No data available.**Bioaccumulative potential****Bioconcentration Factor (BCF)****Product:** No data available.**Partition Coefficient n-octanol / water (log Kow)****Product:** No data available.**Specified substance(s):**

Xylene Log Kow: 3.12 - 3.20

Cumene Log Kow: 3.66



Mobility in soil: No data available.
Other adverse effects: Toxic to aquatic life with long lasting effects.

13. Disposal considerations

Disposal methods: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (Petroleum Distillates), 3, PG III

CFR / DOT:

UN1993, Flammable liquids, n.o.s. (Petroleum Distillates), 3, PG III

IMDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (Petroleum Distillates), 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.



US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Benzene	Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Cumene	5000 lbs.
Toluene	1000 lbs.
Benzene	10 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Fire Hazard
- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard
- Flammable (gases, aerosols, liquids, or solids)
- Acute toxicity (any route or exposure)
- Skin Corrosion or Irritation
- Serious eye damage or eye irritation
- Germ Cell Mutagenicity
- Carcinogenicity
- Specific target organ toxicity (single or repeated exposure)
- Aspiration Hazard
- Hazards Not Otherwise Classified (HNOC)

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

None present or none present in regulated quantities.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
--------------------------	------------------------------------

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
1,2,4-Trimethylbenzene
Xylene
Cumene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
--------------------------	----------------------------



Xylene

Reportable quantity: lbs.

US State Regulations

US. California Proposition 65



WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

1,2,4-Trimethylbenzene
1,3,5-Trimethylbenzene
1,2,3-Trimethylbenzene
Xylene
Cumene

US. Massachusetts RTK - Substance List

Chemical Identity

1,2,4-Trimethylbenzene
1,3,5-Trimethylbenzene
1,2,3-Trimethylbenzene
Xylene
Cumene
Benzene

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

1,2,4-Trimethylbenzene
1,3,5-Trimethylbenzene
1,2,3-Trimethylbenzene
Xylene
Cumene

US. Rhode Island RTK

Chemical Identity

1,2,4-Trimethylbenzene
1,3,5-Trimethylbenzene
1,2,3-Trimethylbenzene
Xylene
Cumene

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable



Kyoto protocol
Not applicable

VOC:
Regulatory VOC (less water and
exempt solvent) : 867 g/l
VOC Method 310 : 98.50 %

Inventory Status:

Australia AICS:	All components in this product are listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	All components in this product are listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	All components in this product are listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	All components in this product are listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.



16. Other information, including date of preparation or last revision

Revision Date: 06/29/2020

Version #: 3.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.