



EUCO[®] DUST-DOWN

ROADWAY DUST CONTROL AGENT

PRODUCT INFORMATION

PACKAGING

Available in 55 gal (208 L) drums, 275 gal (1041L) totes and in bulk

SHELF LIFE

2 years in original unopened container

DESCRIPTION

EUCO DUST-DOWN is a low odor, natural liquid polymer which provides an effective long-lasting method for controlling dust on dirt, gravel, shell, coquina, limestone, clay, sand and marl roads. EUCO DUST-DOWN has natural adhesive properties, which bind surface particles together forming a denser, more compact surface. EUCO DUST-DOWN provides a better driving surface which is less permeable to water, and therefore, less likely to be washed away by rain or moisture uptake.

PRODUCT CHARACTERISTICS

FEATURES & BENEFITS

- Decreases construction site "track out"
- Reduces airborne allergens
- Decreases pot holes and surface break-up
- Decreases vehicle maintenance
- Promotes water conservation
- Reduces soil erosion
- Improves community relations
- Reduces liability
- Cost efficient and labor saving
- Reduces road maintenance

PRIMARY APPLICATIONS

Roads, driveways and parking lots at:

- Ready mix facilities
- Precast plants
- Aggregate manufacturers
- Farms
- Mines
- Construction sites

PRECAUTIONS/LIMITATIONS

- Equipment used to transport EUCO DUST-DOWN should be clean and free of any contaminating residue.
- Water used to dilute EUCO DUST-DOWN should not contain residues or other contaminants.
- The extent of dilution and the application rate should be carefully considered for the intended function.
- Consideration should be given to weather, soil and surrounding conditions.
- Use caution when opening unvented containers as pressure can accumulate.
- Foaming is a characteristic of EUCO DUST-DOWN.
- Care should be taken to maintain EUCO DUST-DOWN above freezing.
- In all cases, consult the Safety Data Sheet before use.

DIRECTIONS FOR USE

A general guide line for one pass is approximately one half ½ gal (1.89 L) of diluted mixture per square yard. Dilution rates may be varied depending on the type of surface being treated.

EUCO DUST-DOWN can be easily applied with conventional spray equipment. Recommended application rate for EUCO DUST-DOWN is 1 gal (3.9 L) of EUCO DUST-DOWN to 10 gal (37.85 L) of water. If applying EUCO DUST-DOWN for the first time, repeat application 3 times (the goal is to reach an absorption depth of three inches). Treated areas will appear darker in color. Reapply when treated area appears to fade or after rain. This will be highly dependent on the amount of traffic.

Clean equipment with plain water.

Rev. 04.21

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.